

SMART UND SWISS SEIT 1876


A 50 AC1 – Two wheel battery sprayer

For professionals from professionals: Powerful (battery) performance for demanding situations – new with CAS power



Two wheel battery sprayer – new with CAS system Electronically pressure controlled, powerful, quiet and environmentally friendly...

The well-proven concept of controlling the pressure by electronics has been complemented by the cross-manufacturer battery pack system. The quick-change system of the CAS battery pack enables uninterrupted working. The electronic control allows to preset the pressure and keeps it at a constant level. The electronic also monitors important components such as the pump and battery pack. A constant pressure results in a constant spray pattern. This maximises effectiveness while reducing the amount of solution used. Depending on the pressure and the accessories used, the battery pack lasts up to 16 hours. During this time, up to 1065 liters can be applied. The A 50 is also equipped with a built-in mixing function.



Real work comfort

- Zero emission, quiet and environmentally friendly
- Robust wheels with locking brake
- 10 m hose, large application radius
- Extensive scope of delivery with 3 nozzle configurations
- Quick-charger
- Holder for storing accessories such as the XL 8 Telescopic lance
- Built-in mixing function



One battery, many solutions CAS SUNDES



- CAS* Unlimited combinations
- Cross-manufacturer compatibility for over 300 devices
- Different battery packs obtainable (up to 10 Ah)
- Charge level is displayed by LED lights
- * CAS (Cordless Alliance System is a cross-manufacturer battery pack system of leading power tool brands)

Unique Birchmeier features

- Constant spray pattern
- · Large filling opening with strainer
- Top quality output assembly
- Robust pump
- Separate drainage opening
- A wide range of accessories
- Mounting plate



Electronically controlled

- · Intellegent pressure control
- Operating pressure adjustable (1 to 10 bar)
- Depending on the pressure and the accessories used, the battery pack lasts from 1 to 16 hours
- · Energy efficient
- Protective setup for pump and battery pack
- Flow rate of up to 3.3 I/min depending on nozzle configuration



Further information

Vario Gun

Spray hood, oval

Fanjet nozzle Art No. 11612810 Duro-mist nozzle a 1.65 mr Art No. 28502325-SB


Anti-drift nozzle

XL 8 S Telescopic lance 7 m Art No. 11935801


Art No. 11889501-SB

Accessories More accessories: www.birchmeier.com

Spray period* A 50 AC1 (2 Duro-mist nozzles 1.5 mm)



Spray output* A 50 AC1 (2 Duro-mist nozzles 1.5 mm)



Technical Specifications A 50 AC1

Tank volume	50 litres		
Pressure range	1 – 10 bar		
Battery pack (with scope of delivery A 50 AC1)	18 V LiHD / 8.0 Ah		
Battery pack charging time	< 160 min		
Nozzle type	Duro nozzle 1.5 mm / Floodjet nozzle 1.6 mm		
Nozzle material	Brass / stainless steel / plastic		
Flow rate (at 1 – 10 bar)	1.1 – 3.3 l/min		
Gaskets	FPM (Viton) / NBR		
Fitting assembly	Screw fitting		
Pump	Diaphragm 12 V DC		
Temperature (min./max.)	5 °C / 30 °C		
Dimensions (H x W x L)	480 x 575 x 1000 mm		
Empty weight with battery pack	33 kg		
Sound pressure level	< 70 dB (A)		

A 50 AC1 (with battery pack 8.0 Ah/charger)	Art.No. 12072701
Battery pack 18 V Li-Power / 2.0 Ah	Art.No. 12070301
Battery pack 18 V Li-Power / 4.0 Ah	Art.No. 12071401
Battery pack 18 V Li-Power / 5.2 Ah	Art.No. 12072501
Battery pack 18 V LiHD / 8.0 Ah	Art.No. 12073601
Battery pack 18 V LiHD / 10.0 Ah	Art.No. 12100701
Quick-charger ASC 55 (230 V)	Art.No. 12070101

	Double nozzle holder with Duro-mist nozzles 1.5 mm	Herbicide floodjet nozzle 1.6 mm	
	I/min	1/min	
1 bar	1.1	1.5	
2 bar	1.5	2.2	
4 bar	2.1	3.0	
6 bar	2.6	3.7	
8 bar	3.0	4.2	
10 bar	3.3	4.2	

Duro-mist nozzle 1.5 mm (additional configuration)				
I/min				
0.6				
0.8				
1.1	. 🛦			
1.3	هر ا			
1.5				
1.7				

Birchmeier «Accu-Power» line










	REB 15 AC1 Art.No. 12070801	REC 15 AC1 Art.No. 12070901	REX 15 AC1 Art.No. 12071001	A 50 AC1 Art.No. 12072701
Tank volume	15 liters	15 liters	15 liters	50 liters
Pressure range	0.5 – 3 bar	0.5 – 6 bar	1 – 10 bar	1 – 10 bar
Spray period per battery pack charging	3.4 h (at 1.5 bar)	12 h (at 1.5 bar)	5.0 h (at 2 bar)	8.1 h (at 2 bar)
Spray output per battery pack charging	93 liters (at 1.5 bar)	270 liters (at 1.5 bar)	390 liters (at 2 bar)	750 liters (at 2 bar)
Stress class*	2	1	1	1

^{* 1 =} Very heavy duty 2 = Heavy duty 3 = Standard duty 4 = Light duty

Your Birchmeier distributor



BIRCHMEIER®

Birchmeier Sprühtechnik AG Im Stetterfeld 1 5608 Stetten Schweiz Telefon +41 56 485 81 81 Fax +41 56 485 81 82

www.birchmeier.com

Art.No. 12089102 | v1221