

SMART UND SWISS SEIT 1876

REX 15 AC1 – Battery backpack sprayer

Powerful, zero emisson and quiet battery backpack sprayer – new with CAS Power



The powerful, zero emisson and quiet REX 15 – new with CAS system: replaces all other small-engine-powered bacpack sprayers

The REX 15 replaces all other small-engine-powered sprayers and has been complemented by the cross-manufacturer battery pack system. The quick-change system of the CAS battery pack enables uninterrupted working. Times of loud and stinking motor sprayers are over, because the Rex 15 is reaching the same spraying performance due to the high-quality battery pack — silent and with zero emissions. In addition, the unit has an electronic pressure control. This ensures to keep the choosen pressure constant and allows - at 10 bar pressure - a spraying performance of more than 0.72 hours. There can be sprayed 120 liters during this time.



Electronically controlled

- Intelligent pressure control
- Operating pressure adjustable (1 to 10 bar)
- Energy efficient
- Protective setup for pump and rechargeable battery pack

Real work comfort

- Zero emission, quiet and environmentally friendly
- Operating pressure can be continuously adjusted
- Flow rate of up to 6 I / min
- Constant and very fine spray pattern
- 2 high performance Duro-mist nozzles
- Optimum comfort to wear due to ergonomic design
- Quick-charger
- Easy access to the suction filter
- No petrol storage neccessary anymore
- Stainless steel hand-cart (available as accessory)




Vario Gun Art.No. 11558501 Bio filter bag Art No. 11475701 Duro-mist nozzle ø 1.5 mm Art No. 28502324-SB Fanjet nozzle Art.No. 11612810 Anti-drift nozzle Art.No. 12009403 XL 8 S Telescopic lance (7 m) Art No. 11935801

Art No

Art.No. 11889501-SB

Stainless steel hand-cart H2 Art.No. 12022601 More accessories: www.birchmeier.com

Spray period* REX 15 AC1 (2 Duro-mist nozzles 1.3 mm) Operating pressure (bar) 8 6 4 2 8.0 Ah 0 10 20 Spray period (hours)



* per battery pack charging

Technical specifications REX 15 AC1

Tank volume	15 liters		
Pressure range	1 – 10 bar		
Battery pack (with scope of delivery REX 15 AC1)	18 V Li-Power / 5.2 Ah		
Battery pack charging time	< 104 min		
Nozzle type	2 Duro-mist nozzles, 1.3 mm		
Nozzle material	Brass / stainless steel		
Flow rate (at 1 - 10 bar)	0.9 - 2.8 I / min		
Gaskets	FPM (Viton) / NBR		
Fitting assembly	Screw fitting		
Pump	Diaphragm pump 12 V DC		
Temperature (min. / max.)	5° C / 30° C		
Dimensions (L x W x H)	290 x 340 x 625 mm		
Empty weight with battery pack	10 kg		
Sound pressure level	< 70 dB (A)		

REX 15 AC1 (with battery pack 5.2 Ah / charger)	Art.No. 12071001		
Battery pack 18 V Li-Power / 2.0 Ah	Art.No. 12070301		
Battery pack 18 V Li-Power / 4.0 Ah	Art.No. 12071401		
Battery pack 18 V Li-Power / 5.2 Ah	Art.No. 12072501		
Battery pack 18 V LiHD / 8.0 Ah	Art.No. 12073601		
Battery pack 18 V LiHD / 10.0 Ah	Art.No. 12100701		
Quick-charger ASC 55 (230 V)	Art.No. 12070101		

Birchmeier «Accu-Power» line














V		d and sub				_
Technical specifications	REB 15 AC1 Art.No. 12070801	REC 15 AC1 Art.No. 12070901	REX 15 AC1 Art.No. 12071001	A 50 AC1 Art.No. 12072701	A 75 AC1 Art.No. 12073801	A 130 AC1 Art.No. 12073901
Tank volume	15 liters	15 liters	15 liters	50 liters	75 liters	130 liters
Pressure range	0.5 – 3 bar	0.5 - 6 bar	1 – 10 bar	1 – 10 bar	1 – 10 bar	1 – 10 bar
Pressure levels	Continuously adjustable	Continuously adjustable	Continuously adjustable	Continuously adjustable	Continuously adjustable	Continuously adjustable
Battery pack	18 V Li-Power / 2 Ah	18 V Li-Power / 4 Ah	18 V Li-Power / 5.2 Ah	18 V Li-Power / 8 Ah	18 V Li-Power / 8 Ah	18 V Li-Power / 8 Ah
Pump performance	3.1 I/min	2.0 I/min	6 I/min	6 I/min	61/min	6 I/min
Max. flow rate*	1.9 I / min	1.4 I/min	2.8 I/min	3.3 I/min	_	_
Nozzle type	Adjustable nozzle 1.7 mm	Adjustable nozzle 1.7 mm	2 Duro-mist nozzles 1.3 mm	2 Duro-mist nozzles 1.3 mm	2	2
Empty weight with battery pack	4.5 kg	5.2 kg	10 kg	33 kg	42 kg ¹	46 kg ¹
Hose length	1.3 m	1.3 m	1.3 m	10 m	50 m	50 m
Dimensions (L x W x H)	240 x 340 x 570	240 x 340 x 570	290 x 340 x 625	480 x 575 x 1000	950 x 680 x 1000	950 x 790 x 1080
Pump	Diaphragm pump 12 V DC	Piston pump 12 V DC	Diaphragm pump 12 V DC	Diaphragm pump 12 V DC	Diaphragm pump 12 V DC	Diaphragm pump 12 V DC
Battery pack charching time	< 80 min	< 80 min	< 104 min	< 160 min	< 160 min	< 160 min
Spray period per battery pack charging**	3.4 h	10 h	5.0 h	8.1 h	-	-
Spread output per battery pack charging**	84 liters	270 liters	390 liters	750 liters	_	_
Stress class***	2	1	1	1	1	1

^{*** 1 =} Very heavy duty 2 = Heavy duty 3 = Standard duty 4 = Light duty

Your Birchmeier distributor



BIRCHMEIER

Birchmeier Sprühtechnik AG Im Stetterfeld 1 5608 Stetten Schweiz Telefon +41 56 485 81 81

Fax +41 56 485 81 82

www.birchmeier.com

¹ Including engine and hose winch ² Standard scope of delivery without spraying equipment