

Super Spray-Matic 1.0 N

# Most durable compression sprayer for aggressive solvents



max.  
3 bar

BMS  
2010  
2023

1



- Transparent 1.2 litre plastic tank with scale and recessed grip
- Special solvent-resistant seals for acetone, nitro thinner etc.
- Adjustable and swivelling brass nozzle (nickel-plated)
- Ergonomic and efficient hand pump up to 3 bar operating pressure
- Large filling opening
- Large distance between tank and handle
- Protected safety valve with venting function
- Available as PA version (PA pump head grey)
- 6 coloured marking rings (optional)



Made in Switzerland

## Convincing performance features

### Super solvent version

Push button lock	Ergonomic and efficient hand pump (grey, PA)
Protected safety and pressure relief valve	Adjustable and swiveling brass nozzle, nickel-plated
Ergonomic closed handle	Colour ring for Fabcoding
Recessed grips	Large filling opening
Large distance between handle and tank	Specially solvent-resistant Gasket (BMS 2010/2023)
Robust plastic tank with 1.0 l filling capacity and max operation pressure of 3 bar	Sucking tube with strainer
Very good stability thanks to special base	dl-scale on tank

**Super Spray-Matic 1.0 N**  
Art.No. 12152101

6 coloured marking rings (optional)  
Ring set (colour coding)  
Art. No. 12164201

## Application <sup>1)</sup>

Chemical resistance			
Solvents	Gasket material / Resistance		
	BMS 2010/2023	FKM (Viton)	EPDM
Mineraloil based solvent (Petroleum, raw petrol, Toluol, Xylol etc.)	<b>very good resistance</b> ✓	limited resistance	not resistant
Ketone (Aceton, Cyclohexanon etc.)	<b>very good resistance</b> ✓	not resistant	not resistant
Alkohole (Propanol, Methanol etc.)	<b>very good resistance</b> ✓	limited resistance	limited resistance

<sup>1)</sup> See also chemistry resistance table „The right sprayer for the right chemistry“.

## Technical specifications

	Super solvent version	Solvent version	Universal version
<b>Products</b>	<b>Super Spray-Matic 1.0 N</b> Art.No. 12152101	<b>Spray-Matic 1.25 N</b> Art.No. 11963301	<b>Spray-Matic 1.25 P</b> Art.No. 11963201
Tank capacity	1.2 l	1.25 l	1.25 l
<b>Pump</b>	<b>PA (grey)</b>	<b>PA (grey)</b>	<b>PP (grey)</b>
<b>Gaskets</b>	<b>Special gasket BMS 2010/2023 <sup>2)</sup></b>	<b>FKM (Viton)</b>	<b>FKM (Viton)</b>
Düsentyp	Brass, nickel plated	Brass	Brass
Max. operating pressure	3 bar	3 bar	3 bar
Weight (empty)	450 g	450 g	450 g
Dimensions	H 285 mm, ø 125 mm	H 305 mm, ø 125 mm	H 305 mm, ø 125 mm

Application: Especially suitable for the automotive industry, motorcycle and bicycle workshops, metalworking industry, do-it-yourselfers

<sup>2)</sup> Especially resistant for mixtures of mineraloil based solvents and ketones (acetone etc.). For example, nitro thinner or brake cleaner.

Further Birchmeier products: [www.birchmeier.com](http://www.birchmeier.com)



**BIRCHMEIER®**

Birchmeier Sprühtechnik AG  
Im Stetterfeld 1  
5608 Stetten  
Schweiz  
Telefon +41 56 485 81 81  
Fax +41 56 485 81 82  
[www.birchmeier.com](http://www.birchmeier.com)